

SPEC. INFO	FL-CC0820-5MX	K66886-S001-B13
		Aug. 30. 2019

1. Model FL-CC0820-5MX
2. Application For 2/3 Format Camera

3. Specification

3-1. Physical (As per the attached drawing)

- (1) Dimensions $\phi 33.0 \text{ mm} \times 43.0 \text{ mm}$
- (2) Weight 78 g
- (3) Mount C-Mount (1 – 32 UN – 2A)
- (4) Filter Screw Size M30.5 mm, P = 0.5 mm

3-2. Optical

- (1) Focal Length 8 mm $\pm 5\%$
- (2) Max. Aperture Ratio 1: 2.0
- (3) Iris Range F / 2.0 to F / 16
- (4) Angle of View
 Diagonal 70.1°
 Horizontal 58.5°
 Vertical 45.3°
- (5) Picture format 8.8 mm $\times$ 6.6 mm
- (6) Focusing Range Inf. to 0.1 m
- (7) Back Focal Length 13.0 mm (in air)
- (8) Flange Back Length 17.526 mm $\pm$ 0.05 mm (in air)

3-3. Mechanical

- (1) Focusing Mechanism
 Rotation Angle 56°
 Rotation Torque 1.0N·cm to 9.0 N·cm
 Focus Ring can be fixed at any positions by
 3 fixing screws or 1 thumb screw (refer to external view)
- (2) Iris Mechanism
 Non-click
 Rotation Angle 83°
 Rotation Torque 0.01N·cm to 3.0 N·cm
 Iris Ring can be fixed at any positions by 3 fixing screws
 or 1 thumb screw (refer to external view)

3-4. Vibration & Shock Test Standard

(1) Vibration Conditions

Wave	Sine Wave
Acceleration	1.96 m/s ² to 59.78 m/s ²
Cycle Range	10 Hz to 55 Hz
Cycle Period	3 Minutes
Duration of Vibration	120 Minutes Respectively in Three Dimensional Directions

(2) Shock Conditions




Tester	Shock Testing Machine by Dropping
Impact Force	588 m/s ²
Duration of Shock	3.5 ms
Directions & Number of Times	1 Time Respectively in Three Dimensional Directions

SPEC. INFO	FL-CC0820-5MX	K66886-S001-B23
		Aug. 30. 2019

3-5. Environmental Temperature Range -10°C to $+50^{\circ}\text{C}$

4. Accessories

(1) Front Lens Cap	1 piece	
(2) Rear Lens Cap	1 piece	
(3) Fixing Screw for Focus ,Iris Ring	6 pieces	
(4) Thumbscrew for Focus ,Iris Ring	2 pieces	(for Optional Usage)
(5) Instruction Manual	1 sheet	
(6) Packing Box	1 piece	



SPEC. INFO	FL-CC0820-5MX
	K66886-S001-B33
RICOH Industrial Solutions Inc. Aug.30.2019	